



## E25BMHL

The ENDURO engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.



TECHNICAL CHARACTERISTICS	E25BMHL
<b>MOTOR</b>	
Engine Type	In-line 2
Reduction ratio	6.2 :1
Start-up	Manual
Power system	1 Carburetor
Lubrication system	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	11.0 L/h @5500 tr/min
Fuel	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500
Max.Prop Shaft Horsepower (Kw)	18.4 Kw (25 hp)
Bore x Stroke (mm)	72.0 X 61.0
Architecture	L2
Displacement (cc)	496
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	80 W
Control	Tiller handle
<b>DIMENSIONS</b>	
Engine transom height (mm)	L: 550 (21.7 in)
Dry weight with propeller (kg)	57
<b>EQUIPMENT</b>	
Service kit assy.	✓
Fuel Tank comp.	✓
Fuel Pipe Comp.	✓
<b>REGULAR PROPELLER (3 blades)</b>	
Material	ALUMINUM
Diameter	9 7/8

Always wear a helmet, eye protection and protective proper clothing.

CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

