



«ENDURO» engines, absolute workhorses, offer unrivalled performance for your money and can withstand the toughest usage conditions. All good reasons to explain why YAMAHA Enduro boats for decades.

## E60HMHDL/E60HMHDX



TECHNICAL CHARACTERISTICS	E60HMHDL	E60HMHDX
<b>MOTOR</b>		
Engine Type	In-line 2	In-line 2
Reduction ratio	6.1 :1	6.1 :1
Start-up	Manual	Manual
Power system	3 Carburetors	3 Carburetors
Lubrication system	Pre-Mixing 2 %	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	25.5 L/h @5500 tr/min	25.5 L/h @5500 tr/min
Fuel	Regular Gasoline	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500	4500-5500
Max.Prop Shaft Horsepower (Kw)	44.1 (60 hp)	44.1 (60 hp)
Bore x Stroke (mm)	72.0 X 69.5	72.0 X 69.5
Architecture	L3	L3
Displacement (cc)	849	849
<b>MORE</b>		
Propeller Rotation	Clockwise	Clockwise
Alternator	80 W	80 W
Control	Tiller handle	Tiller handle
<b>DIMENSIONS</b>		
Engine transom height (mm)	L: 571 mm (22.5 in)	X: 648 mm (25.5 in)
Dry weight with propeller (kg)	105	105
<b>EQUIPMENTS</b>		
Service kit assy.	✓	✓
Fuel Tank comp.	✓	✓
Fuel Pipe Comp.	✓	✓
<b>REGULAR PROPELLER (3 blades)</b>		
Material	ALUMINUM	ALUMINUM
Diameter	14	14

Always wear a helmet, eye protection and protective proper clothing.  
CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

